

## Product Discontinuation Notices

July 4, 2011

Programmable Controllers

No. 2011201E

### Discontinuation Notice of Controller Link Unit (CS1W-CLK[ ]-V1, CJ1W-CLK21-V1) and Controller Link Support Board (3G8F7-CLK[ ]-EV1)

#### Product Discontinuation



CS1W-CLK[ ]-V1  
CJ1W-CLK21-V1  
3G8F7-CLK[ ]-EV1



#### Recommended Replacement

CS1W-CLK[ ]3  
CJ1W-CLK23  
3G8F7-CLK[ ]3-E

**Discontinuation date : The end of July, 2012**

#### Caution on recommended replacement

CS1W-CLK23/13/53, CJ1W-CLK23 and 3G8F7-CLK23-E/13-E/53-E are upward compatible with each discontinuation models.

#### Difference from discontinued product

Model	Body Color	Dimensions	Wire connection	Mounting Dimensions	Characteristics	Operation ratings	Operation methods
CJ1W-CLK23	**	**	**	**	**	**	**
CS1W-CLK23/13/53	**	**	**	**	**	**	**
3G8F7-CLK23/13/53	**	**	**	**	**	**	**

\*\* : Fully compatible

\* : The change is a little/Almost compatible

-- : Not compatible

- : No corresponding specification

## Product Discontinuation and recommended replacement

Product discontinuation	Recommended replacement
CS1W-CLK21-V1	CS1W-CLK23
CS1W-CLK12-V1	CS1W-CLK13
CS1W-CLK52-V1	CS1W-CLK53
CJ1W-CLK21-V1	CJ1W-CLK23
3G8F7-CLK21-EV1	3G8F7-CLK23-E
3G8F7-CLK12-EV1	3G8F7-CLK13-E
3G8F7-CLK52-EV1	3G8F7-CLK53-E

## Specifications

### Controller Link Unit

	Product discontinuation	Recommended replacement
	<b>CJ1W-CLK21-V1</b> <b>CS1W-CLK21-V1</b> <b>CS1W-CLK12-V1</b> <b>CS1W-CLK52-V1</b>	<b>CJ1W-CLK23</b> <b>CS1W-CLK23</b> <b>CS1W-CLK13</b> <b>CS1W-CLK53</b>
Maximum number of data link words (data link area for sending/receiving that is created for a single node in a single CPU Unit)	20,000 words max.	
Number of send words per node (total of area 1 and area 2)	1,000 words max.	4,000 words max.
Maximum number of error log	39	64

### Controller Link Support Board

	Product discontinuation	Recommended replacement
	<b>3G8F7-CLK21-EV1</b> <b>3G8F7-CLK12-EV1</b> <b>3G8F7-CLK52-EV1</b>	<b>3G8F7-CLK23-E</b> <b>3G8F7-CLK13-E</b> <b>3G8F7-CLK53-E</b>
Support OS	Windows XP, 2000 (Only 32 bit version)	Windows7, Vista, XP, 2000 (Only 32 bit version)
Number of send words per node (total of area 1 and area 2)	1,000 words max.	4,000 words max.
Maximum number of error log	39	64