

Product Discontinuation Notices



NULLES

July 4, 2011

Programmable Controllers

No. 2011196E

Discontinuation Notice of Controller Link Support Board (ISA-bus) 3G8F5-CLK21-E1 and Controller Link Support Software

Product Discontinuation

Recommended Replacement



3G8F5-CLK21-E C200HW-ZW3AT2-EV2



3G8F7-CLK23-E CXONE-AL01D-V4

Discontinuation date : The end of July, 2012

Caution on recommended replacement

3G8F7-CLK23-E is Controller Link Support Board for PCI bus interface. FinsGatewayVersion2003 is included.

Difference from discontinued product

| Model | Body Color | Dimen sions | Wire connection | Mounting Dimensions | Charact eristics | Operation ratings | Operation methods |
|---------------|---------------|----------------|-----------------|------------------------|---------------------|----------------------|----------------------|
| 3G8F7-CLK23-E | - | - | ** | - | ** | ** | * |

** : Fully compatible

* : The change is a little/Almost compatible

-- : Not compatible

- : No corresponding specification

Product Discontinuation and recommended replacement

| Product discontinuation | Recommended replacement |
|-------------------------|-------------------------|
| 3G8F5-CLK21-E | 3G8F7-CLK23-E |
| C200HW-ZW3AT2-EV2 | CXONE-AL01D-V4 |

OMRON Corporation Industrial Automation Company

Differences of specifications

3G8F7-CLK23-E has compatibility with 3G8F5-CLK21-E. The differences of specifications are as follows.

| | Product discontinuation | Recommended replacement | |
|-------------------------------|--|--|--|
| | 3G8F5-CLK21-E | 3G8F7-CLK23-E | |
| PC interface | ISA bus | PCI bus | |
| Attached software | Driver software for PC-AT | Driver software for Windows | |
| | Controller Link Support Software (for PC-AT) | (FinsGatewayVersion2003) | |
| Controller Link communication | Maximum number node: 32 | Maximum number of node: 62 | |
| | Datalink function Maximum number of sending words per node: 1000CH | Datalink function Maximum number of sending words per node: 4000CH | |
| | Maximum number of error log: 39 | Maximum number of error log: 64 | |